



CC-BC 4 M

Battery Charger

Item No.: 1002221

Ident No.: 11016

Bar Code: 4006825614275

DRAFT

The Einhell CC-BC 4 M Battery Charger is an intelligent, micro-processor controlled system with multi-stage charging cycle. It is suitable for all standard 6V/12V vehicle batteries. The trickle charge function does not harm the battery being charged and prolongs battery life, particularly on seasonal vehicles. Over-discharged batteries can be restored with the rescue function. Over-charge, short circuit and reverse polarity protection and the dust and splash water proof case with integrated bracket for wall mounting prevent damage to the charger. The unit also comes with fully insulated terminal clamps. The LED battery voltage and charge status display show at a glance the current state of the battery.

Features

- Intelligent battery charger with microprocessor controller
- Universal battery charger for various battery types such as:
 - Gel, AGM, zero and low maintenance lead-acid batteries, etc...
- Automatic battery voltage adjustment for 6/12V vehicles
- Protection type: IP65 (protected against dust and splash water)
- Trickle charge function for a continuously ideal charge status
- Use will extend the life of the battery
- Winter charging mode for outdoor temperatures below 5°C
- Display: LCD battery voltage and charging progress display
- Rescue function for exhausted batteries
- Automatic protec.against overcharging,short-circuit&swapped poles
- Totally insulated battery terminals and integrated wall bracket
- Multi-step charging cycle, contr. and monitored by microprocessor
- Optimal for season.vehicles with long idle times(convert./m-bike)



Technical Data

- Mains supply 220-240 V | 50/60 Hz
- Charging voltage 6 V/ 12V
- Suitable for batteries (from min. Ah to max. Ah): 3 - 120 Ah
- Charging current Min. (arith./eff.) - Max. 2 / [-] A (arith./eff.) on 6 V d.c.
- Charging current Min. (arith./eff.) - Max. 2 / [-] - 4 / [-] A (arith./eff.) on 12 V d.c.

Logistic Data

- Product weight 0 kg
- Gross weight single packaging 0 kg
- Dimensions single packaging 0 x 0 x 0 mm
- Pieces per export carton 12 Pieces
- Gross weight export carton 0 kg
- Dimensions export carton 410 x 240 x 270 mm
- Container quantity (20"/40"/40"HC) 11520 | 23808 | 26784