

## Heating Generator HGG 110 EX

Art.-No.: 23.301.26

Bar code: 4006825532579

Sales unit: 1 pc

Due to the high efficiency design of the unit it could be kept small and handy with a high output. The connection takes place on a normal 5 resp. 11 kg propane/butane gas bottle. The integrated Piezo ignition as well as the thermal cut-out against over heating cut off the gas and warrant a safe operation. The gas hose and the pressure reducer are not supplied as standard equipment.

Unit is not to be used for professional service!

For professional service to be used only in connection with gas hose rupture device (special accessory) according DIN 30693

### Features:

- ON/OFF-switch for fan
- Gas valve button
- Heating reflector made of galvanized sheet steel (1)
- Carrying handle (2)
- Housing made of varnished sheet steel (3)
- Piezo ignition (4)
- Back-fire safety device
- Piezo electrical flame safety
- Solenoid valve
- Mains cable

### Technical data:

- |                               |                        |
|-------------------------------|------------------------|
| - Mains:                      | 230 V ~ 50 Hz 38 W     |
| - Nominal heat load:          | 11.2 kW                |
| - Nominal air volume:         | 500 m <sup>3</sup> /h  |
| - Nominal gas consumption:    | 815 g/h liquid gas P/B |
| - Operating pressure:         | 300 mbar               |
| - Type of gas propane/butane: | Class I.3              |
| - Weight:                     | 5.7 kg                 |
| - Packing dimensions:         | 400 x 230 x 310 mm     |



As special accessory available:

Gas hose rupture device

Art.-No.: 33.912.30

Bar code: 4006825338348