

Bar Code: 4006825611632

The TC-AC 400/50/8 compressor is an efficient and robust endurance runner for high requirements. The high-quality components and oil lubrication ensure a very long service life. The oil level can be checked quickly and easily using the oil-level glass. The working pressure of up to 8 bar can be set to many applications using the pressure reducer. Sufficient reserves of compressed air for every application are held ready by the 50 liter tank. A pressure switch, a non-return and a safety valve ensure the safe operation of the TC-AC 400/50/8, while the large wheels and robust handle enable easy transport. The solid, long-lasting tank comes with a 10-year guarantee against rusting through.

Features

- Long-lasting, oil-lubricated pump
- 50l tank
- Oil level check by oil-level glass
- Pressure reducer can be set for working pressures up to 8 bar
- Pressure gauge & quick-release coupling for controlled pressure
- Pressure gauge & quick-release coupling for uncontrolled pressure
- Easily accessible intake filter
- Pressure switch, non-return and safety valve
- Drain cock
- Transport handle and 2 large wheels for easy transport
- 10 year warranty against rusting through of the tank

Technical Data

- Mains supply	230 V 50 Hz
- Max. engine power (S3 S3%)	2200 W 50 %
- Engine speed	2850 min^-1
- Suction capacity	400 L/min
- Output power at 0 bar	319 L/min
- Output power at 4 bar	207 L/min
- Output power at 7 bar	176 L/min
- Max. operating pressure	8 bar
- Number of cylinders	2 Pieces
- Tank volume	50 L

Logistic Data

- Product weight
- Gross weight single packaging
- Dimensions single packaging
- Pieces per export carton
- Gross weight export carton
- Dimensions export carton
- Container quantity (20"/40"/40"HC)

38.4 kg 43.25 kg 770 x 350 x 670 mm 1 Pieces 43 kg 770 x 350 x 670 mm 144 | 297 | 396



Illustrations can contain accessories, which are not included in standard extent of delivery Illustration similar (in design), production-wise modifications reserve GS mark belongs to the product itself only, excluded accessory Generated at: 21.10.2015 09:21 Page

FASY READ