



**Rain Barrel Pump** 

**GE-PP 5555 RB-A** 

Item No.: 4170425

Ident No.: 11019

Bar Code: 4006825648690

The GE-PP 5555 RB-A submersible pressure and rainwater barrel pump can be used with flexibility, both in cisterns or wells, in rainwater containers and for supplying service water as well. The multi-stage pump drive generates high delivery pressure and the innovative automatic function with integrated dry-run safeguard switches the equipment on whenever required and then off again automatically as well. The system is rounded off with an infinitely adjustable telescopic extension tube with movable water connection and a practical holder, integrated cable rewind on the housing and an ergonomic carry-handle. For guaranteed high quality and a long service life, the pump has a high-grade mechanical seal and robust plastic housing.

## Features & Benefits

- 2in1 combination pump pressure + rainbarrel pump one device
- Automatic function with dry-run protection
- Multi-stage pump impeller for high delivery pressure
- Infinitely adjustable telescopic connection pipe
- Flexible swan-neck with hose connection
- Integrated cable storage holder
- High-quality mechanical sealing for a long life
- Pump housing made of impact-resistant plastic
- Easily accessible hose connection on top of the pump
- Ergonomic carry handle

## **Technical Data**

230-240 V | 50 Hz - Mains supply 550 W - Power - Max. delivery capacity 5500 L/h - Max. delivery height 20 m - Max. immersion depth 7 m - Max. water temperature 35 °C - Max. size of foreign particles  $0 \, \text{mm}$ 

- Hose connection 33,3mm (G1 AG) - Power cord 1000 cm | H05RN-F

## **Logistic Data**

- Product weight 5 kg - Gross weight single packaging 7.05 kg

- Dimensions single packaging 280 x 200 x 408 mm

- Pieces per export carton 4 Pieces - Gross weight export carton 28.9 kg

560 x 420 x 420 mm - Dimensions export carton - Container quantity (20"/40"/40"HC) 1100 | 2300 | 2800



















