



Einhell

ACCESSORY



PXC-Starter-Kit

2x 5,2Ah & Twincharger Kit

Item No.: 4512108


Ident No.: 21010

Bar Code: 4006825652376

The Einhell 18V 2x5.2Ah PXC Starter Kit is the ideal basis for starting or expanding the Power X-Change range in your home. A single rechargeable battery and a single charger for all tools not only saves significant costs of buying, universal use also helps protect the environment and provides flexibility. For high Power, long + sustained working time and to use 36V (2x18V) devices, two Batteries are included. The ABS process-controlled active battery management system ensures maximum safety, optimum tool performance, maximum operating time and a maximum service life. The high-speed charging technology means short charging times, and for optimum charging and maximum safety the battery is permanently monitored by a charging management system

Features & Benefits

- Universal usability for all Power X-Change rechargeable devices:
- Saving money, protecting the environment, and flexibility
- Longer working time and more power with 2x 18V batteries (= 36V)
- Battery features:
- PLUS-technology: extra power for intensive operation
- The ABS process-controlled battery management system stands for
- max. safety, optimum performance, operating time + lifetime
- Freedom of cordless operation: No tangled cables and free working
- High-quality Li-Ion cells means no memory effect,
- low self-discharge and high, constant power
- Current charge level indicated by 3-stage LED display
- Impact protection and good grip thanks to rubber-coated housing
- Trough handle for easy removal
- Housing protected against dust, corrosion and mechanical damage
- Suitable for TWIN-PACK use in power demanding 36V applications
- Charger features:
- Parallel Charging of 2x 18V batteries saves space,
- provides fast + high availability and continuous working
- Quick-charge technology ensures short charging times
- Permanent battery monitoring for optimum charging
- Refresh mode allows deeply discharged batteries to be reactivated
- Maximum safety due to intelligent charge management
- Current information on 6-stage status LED display
- Integrated suspension eyelets for user-friendly wall-mounting



Technical Data

- Mains supply charger	220-240 V 50-60 Hz
- Voltage output charger	18 V
- Charging time	100min
- Voltage	18 V
- Battery capacity	5200 mAh
- Max. power	1260 W
- Amount of batteries	2 Pieces



Logistic Data

- Product weight (kg)	1.79
- Gross weight (kg)	2.92
- Dimensions single packaging	282 x 87 x 294 mm
- Pieces per export carton	6 Pieces
- Gross weight of export carton	18 kg
- Dimensions export carton	620 x 295 x 325 mm
- Container quantity (20"/40"/40"HC)	2724 5652 6762